



# REPORT

Contact person  
Nata Amiryarahmadi  
Sustainable Built Environment  
+46 10 516 54 37  
Nata.amiryarahmadi@sp.se

Date  
2016-07-28

Reference  
6P06299-B

Page  
1 (4)

Strand Design Design AB  
J.A Pripps Gata 2,  
42132 Västra Frölunda

## Noise screening effect of “Nunna” chairs

### Client

Strand Design Design AB by Charles Strand.

### Test object

“Nunna” chair Strand Design AB.

Pictures of the test object can be seen in the report.

### Date of test

July 27, 2016

### Measurement procedure

The screening effect of the chair is of interest with respect to reducing the outside noise at the seating position, as well as providing privacy for the seated person by reducing the transmission of speech to the outside. To show these screening effects of the chair, two measurement setups were used. First, the loudspeaker was placed at ear height of a seated person, 2.5 m away from the seating position of the chair, and the noise emitted by the loudspeaker was measured at ear positions inside the chair at two different depths. In the next set of measurements, the loudspeaker was placed inside the chair at a position representing the mouth of a seated person with medium height (170 cm). The microphone was placed outside the chair, at 2.5 m distance, in front of the loudspeaker. The loudspeaker generated pink noise with adjacent third-octave bands difference less than 5 dB.

In order to show the angle-dependent screening effect, the chair was rotated between 0 to 180 degrees in 45° steps and the measurements were repeated for every angle. All measurements were performed at the semi-anechoic laboratory of SP Sound and Vibration.

### Results

Table 1 and 2 show the measurement results corresponding to all sets of measurements. The data are presented for two frequency ranges, 50-10000 Hz range which makes the results comparable with the absorption measurement data, and 200-2000 Hz which is a critical frequency range concerning human speech.

---

#### SP Technical Research Institute of Sweden

*Postal address*

SP  
Box 857  
SE-501 15 BORÅS  
Sweden

*Office location*

Brinellgatan 4  
SE-504 62 BORÅS

*Phone / Fax / E-mail*

+46 10 516 50 00  
+46 33 13 55 02  
info@sp.se

This document may not be reproduced other than in full, except with the prior written approval of SP.

Table 1 – Equivalent A-weighted sound pressure levels at different angles. Noise source outside, and receiver inside the chair.

		Microphone at ear position inside the chair*					
		Angle	0°	45°	90°	135°	180°
		Depth**					
$L_{Aeq, 50-10000}$ (dBA)	15 cm		78.0	73.8	67.3	62.0	61.3
	30 cm		76.3	76.0	74.3	65.4	62.2
$L_{Aeq, 200-2000}$ (dBA)	15 cm		75.6	71.1	64.7	58.6	55.5
	30 cm		72.5	72.1	70.9	62.4	58.8

\* The presented value is the average between  $L_{Aeq}$  at both ears.

\*\* The depths are measured from the back of the chair.

Table 2 – Equivalent A-weighted sound pressure levels at different angles. Sound source inside, and receiver outside the chair.

		Loudspeaker at mouth position inside the chair*					
		Angle	0°	45°	90°	135°	180°
		Range					
$L_{Aeq, 50-10000}$ (dBA)			75.6	66.8	61.6	59.2	58.8
$L_{Aeq, 200-2000}$ (dBA)			72.8	65.6	59.5	56.4	55.6

\* The loudspeaker was placed at the depth 28 cm from the back of the chair and at 65 cm height from the seating surface.